

# OPTIGREEN FKD 10

## Protection and Drainage Board

Made from deep-drawn HDPE with no water reservoir function with channel system on the upper side and fleece lining for drainage under flagging on roof areas. Use also as vertical building drainage.



<b>Material</b>	Recycled HDPE (napped sheet) PP (fleece)
<b>Nominal thickness</b>	approx. 10 mm
<b>Grammage</b>	approx. 750 g/m <sup>2</sup> (total) approx. 615 g/m <sup>2</sup> (napped sheet) approx. 135 g/m <sup>2</sup> (fleece)
<b>Colour</b>	grey/black
<b>max. compressive strength</b>	Approx. 400 kN/m <sup>2</sup> (40 t/m <sup>2</sup> ) with 18 % compression (in accordance with DIN EN ISO 25619-2) approx. 185 kN/m <sup>2</sup> with 10 % compression
<b>Filter fleece</b>	PP thermally strengthened, GRC 2, flow rate with 100 mm water column 75 l/m <sup>2</sup> x s
<b>Water discharge capacity (DIN EN ISO 12958)</b>	Measured at: $\sigma = 20$ kPa, soft/hard, MD, with filter fleece on the upper side: i = 0.01 (=1 % roof pitch): 0.33 l/(m*s) i = 0.02 (=2 % roof pitch): 0.45 l/(m*s) i = 0.05 (=5 % roof pitch): 0.71 l/(m*s) i = 1 (vertical): 3.50 l/(m*s)
<b>Reduction in foot fall sound inspected in accordance with EN ISO 10140 assessed in accordance with ISO 717-2</b>	Improvement in foot fall sound for the following layer structures: $\Delta Lw$ 29 dB RMS 950 TS, FKD 10, 40 mm chippings, 40 mm concrete slab
<b>Quantity/delivered unit</b>	25 m <sup>2</sup> /roll = 2.0 x 12.5 m Coverage dimensions 24.0 m <sup>2</sup> /roll 150 m <sup>2</sup> /pallet
<b>Delivery form</b>	according to size of order
<b>Delivery weight</b>	approx. 19.0 kg/roll approx. 138 kg/disposable pallet
<b>Pack size</b>	Diameter approx. 0.40 m, height approx. 2.0 m / per roll

### Area of use

- As a drainage element under floor surfaces used on foot
- As a drainage element under vegetation areas with no need for water reservoir but increased pressure load
- Vertically along ascending, filled structural components or as foundation wall drainage
- Use only on roof surfaces with a minimum of 2% regular gradient of the sealing plane

### Specific properties

- 100% recycled HDPE
- CE-marked CE-1213-CPR-5584
- Pressure stable
- Prevents accumulation of water
- Lightweight super structure with high drainage capacity
- Compressive strength approx. 400 kN/m<sup>2</sup> (40 t/m<sup>2</sup>)
- Thermally strengthened filter fleece layer with 75 l/m<sup>2</sup> x s flow rate with 100 mm water column.
- Recyclable

The preceding details are guideline values established under laboratory conditions. These values are subject to a certain manufacturing tolerance. The data contained in this product information sheet represents Optigreen's technical knowledge at the time of publication. Optigreen reserves the right to change and update details in accordance with new insights and to modify specified properties accordingly. No liability accepted for misprints.

### Optigrün international AG

Am Birkenstock 15 – 19,  
72505 Krauchenwies-Göggingen  
Tel. +49 7576 772-0, Fax +49 7576 772-299, info@optigruen.de

### Optigreen Limited (Service UK only)

Suite G5 Albany Chambers, 26 Bridge Road East  
Welwyn Garden City (Herts), AL7 1HL  
Phone +44 203 5899400, Fax +44 207 1171664, info@optigreen.co.uk

